



MultiRAE Pro

Wireless Portable Multi-Threat Radiation and Chemical Detector



The MultiRAE Pro is the industry's only portable wireless multi-threat monitor. The MultiRAE Pro's ability to simultaneously detect gamma radiation and toxic industrial chemicals (TICs/TIMs) enables responders to reduce the equipment footprint and achieve greater agility when operating downrange.

The MultiRAE Pro's optional wireless capability improves safety by providing commanders and safety officers real-time access to instrument readings and alarm status from any location¹ for better situational awareness and faster incident response.

- Detector of choice for government agencies and top HazMat teams worldwide
- Highly versatile and customizable
- Man Down Alarm with real-time remote wireless notification
- Compliant with MIL-STD-810G and 461F performance standards
- Fully automatic bump testing and calibration with AutoRAE 2

KEY FEATURES

Wireless. Versatile. Proven.

- All-in-one monitoring capabilities for radiation, VOCs, oxygen, toxic and combustible gases, up to 6 threat types at a time²
- Over 25 interchangeable sensor options, including parts-per-billion PID and gamma radiation
- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions
- Intelligent sensors store calibration data, so they can be swapped in the field³
- Large graphical display with easy-to-use, icon-driven user interface

APPLICATIONS

- Civil defense (search and rescue)
- Homeland security
- HazMat response
- Military
- Semiconductor manufacturing
- Environmental



CBRN detection with the MultiRAE Pro

MIL-STD-461F

MIL-STD-810G



AutoRAE 2
Compatible



ATEX

IECEx



MultiRAE Pro



Wireless Portable Multi-Threat Radiation and Chemical Detector

SPECIFICATIONS

Instrument Specifications⁴

Size	7.6" H x 3.8" W x 2.6" D (193 x 96.5 x 66 mm)
Weight	31 oz (880 g)
Sensors	Over 25 intelligent interchangeable field-replaceable sensors including gamma radiation, ppb and ppm PID sensors for VOCs, electrochemical sensors for toxic gases and oxygen, combustible LEL and NDIR sensors, and CO ₂ NDIR sensor
Battery Options, Runtime ⁵ and Recharge Time	- Rechargeable Li-ion (~12-hr. runtime, < 6-hr. recharge time) - Extended duration Li-ion (~18-hr. runtime, < 9-hr. recharge time) - Alkaline adapter with 4 x AA batteries (~6-hr. runtime)
Display	Monochrome graphical LCD display (128 x 160) with backlighting Automatic screen "flip" feature
Display Readout	- Real-time reading of gas concentrations; PID measurement gas and correction factor; Man Down Alarm on/off; visual compliance indicator; battery status; datalogging on/off; wireless on/off and reception quality. - STEL, TWVA, peak, and minimum values
Keypad Buttons	3 operation and programming keys (Mode, Y/+, and N/-)
Sampling	Built-in pump. Average flow rate: 250 cc/min. Auto shutoff in low-flow conditions
Calibration	Automatic with AutoRAE 2 Test and Calibration System or manual
Alarms	Wireless remote alarm notification; multi-tone audible (95 dB @ 30 cm), vibration, visible (flashing bright red LEDs), and on-screen indication of alarm conditions - Man Down Alarm with pre-alarm and real-time remote wireless notification
Datalogging	Continuous datalogging (6 months for 5 sensors at 1-minute intervals, 24/7) - User-configurable datalogging intervals (from 1 to 3,600 seconds)
Communication and Data Download	- Data download and instrument set-up and upgrades on PC via desktop charging and PC comm. cradle, travel charger, or AutoRAE 2 Automatic Test and Calibration System - Wireless data and alarm status transmission via built-in RF modem (optional)
Wireless Network	ProRAE Guardian Real-Time Wireless Safety System or EchoView Host-based Closed-Loop System
Wireless Frequency and Approvals ⁶	ISM license free band, 868Mhz or 900Mhz FCC Part15, CE R&TTE, ANATEL
Wireless Range (Typical)	MultiRAE Pro to RAElink3 [Z1] Mesh modem ~330 feet (100 meters) MultiRAE Pro to EchoView Host, RAEMesh Reader or RAEPoint ~660 feet (200 meters)
Operating Temperature	-4° to 122°F (-20° to 50°C)
Humidity	0% to 95% relative humidity (non-condensing)
Dust and Water Resistance	IP-65 ingress protection rating
Hazardous Location Approvals	CSA: Class I, Division 1, Groups A, B, C and D, T4 Class II, Division 1, Groups E, F, G T85°C ATEX: 0575 II 1G Ex ia IIC T4 Ga 2G Ex ia d IIC T4 Gb with IR Sensor installed I M1 Ex ia I Ma IECEX: Ex ia IIC T4 Ga Ex ia d IIC T4 Gb with IR Sensor installed I M1 Ex ia I Ma IECEX/ANZE: Ex ia IIC T4 Ga Ex ia d IIC T4 Gb with IR Sensor installed Ex ia I Ma
CE Compliance (European Conformity)	EMC directive: 2004/108/EC. R&TTE directive: 1999/5/EC. ATEX directive: 94/9/EC
EMI/RFI ⁵	No effect when exposed to 0.43mW/cm ² RF interference from a 5-watt transmitter at 12" (30cm)
Performance Tests	MIL-STD-810G and 461F compliant. LEL CSA C22.2 No. 152; ISA-12.13.01
Languages	Arabic, Chinese, Czech, Danish, Dutch, English, French, German, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, and Turkish
Warranty	- Two years on non-consumable components and catalytic LEL, CO, H ₂ S, and O ₂ sensors - One year on all other sensors, pump, battery, and other consumable parts

Sensor Specifications⁴

Radiation Sensor	Range	Sensor Type
Gamma	0 to 20,000 µRem/h (dose rate)	1cc Cst (TI) scintillator with photodiode
PID Sensors	Range	Resolution
VOC 10.6 eV (Ext. Range)	0 to 5,000 ppm	0.1 ppm
VOC 10.6 eV (ppb)	0 to 2,000 ppm	10 ppb
Combustible Sensors	Range	Resolution
Catalytic LEL	0 to 100% LEL	1% LEL
NDIR (0-100% LEL Methane)	0 to 100% LEL	1% LEL
NDIR (0-100% Vol. Methane)	0 to 100% Vol.	0.1% Vol.
Carbon Dioxide Sensor	Range	Resolution
Carbon Dioxide (CO ₂) NDIR	0 to 50,000 ppm	100 ppm
Electrochemical Sensors	Range	Resolution
Ammonia (NH ₃)	0 to 100 ppm	1 ppm
Carbon Monoxide (CO)	0 to 500 ppm	1 ppm
Carbon Monoxide (CO), Ext. Range	0 to 2,000 ppm	10 ppm
Carbon Monoxide (CO), H ₂ -comp.	0 to 2,000 ppm	10 ppm
Carbon Monoxide (CO) + Hydrogen Sulfide (H ₂ S) Combo	0 to 500 ppm 0 to 200 ppm	1 ppm 0.1 ppm
Chlorine (Cl ₂)	0 to 50 ppm	0.1 ppm
Chlorine Dioxide (ClO ₂)	0 to 1 ppm	0.03 ppm
Ethylene Oxide (EtO-A)	0 to 100 ppm	0.5 ppm
Ethylene Oxide (EtO-B)	0 to 10 ppm	0.1 ppm
Formaldehyde (HCHO)	0 to 10 ppm	0.05 ppm
Hydrogen Cyanide (HCN)	0 to 50 ppm	0.5 ppm
Hydrogen Sulfide (H ₂ S)	0 to 100 ppm	0.1 ppm
Methyl Mercaptan (CH ₃ -SH)	0 to 10 ppm	0.1 ppm
Nitric Oxide (NO)	0 to 250 ppm	0.5 ppm
Nitrogen Dioxide (NO ₂)	0 to 20 ppm	0.1 ppm
Oxygen (O ₂)	0 to 30% Vol.	0.1% Vol.
Phosphine (PH ₃)	0 to 20 ppm	0.1 ppm
Sulfur Dioxide (SO ₂)	0 to 20 ppm	0.1 ppm

- 1 Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.
- 2 A two-gas combination sensor is required for a 6-gas configuration.
- 3 RAE Systems recommends calibrating sensors on installation.
- 4 Specifications are subject to change.
- 5 Specification for non-wireless monitors.
- 6 Please contact RAE Systems for specific wireless approvals

ORDERING INFORMATION (MODEL: PGM-6248)

- Wireless¹ and non-wireless configurations are available
- Refer to the Portables Pricing Guide for part numbers for monitors, accessories, sampling and calibration kits, gas sensors, and replacement parts

CORPORATE HEADQUARTERS

RAE Systems by Honeywell
3775 North First Street
San Jose, CA 95134 USA
RAE-InsideSales@honeywell.com

DS-1068-06

WORLDWIDE SALES OFFICES

USA/Canada 1.877.723.2878
Europe +45.86.52.51.55
Middle East +00971.4.440.5949
China +86.10.5885.8788-3000
Asia Pacific +852.2669.0828

www.raesystems.com