

Go-CAL™

Air Flow Calibrator



- Precision air flow calibration between 0.01 - 20 LPM
- Continuous real-time air flow display
- Battery powered, compact, and lightweight for field portability
- NIST traceable calibration certificate included
- Calibrator kit ships complete for immediate use

The Go-Cal™ air flow calibrator is a portable, battery-operated calibrator that is lightweight, easy to use, and accurate within 2% of reading. Go-Cal™ displays air flow rate continuously allowing adjustments to pump flow-rate in real-time. The Go-Cal™ displayed flowrate is compensated for temperature making it easier to produce consistent results at various calibration locations.

Description	Part Number
Go-Cal Air Flow Calibrator Kit	811-9916-01
Go-Cal Replacement Battery Pack	811-9917-03
Go-Cal Replacement Filter	811-9917-01
Go-Cal Replacement Tubing Kit	811-9917-02
Go-Cal Dampening Module	811-9917-05
Go-Cal Carrying Case, Soft	811-9917-04
Go-Cal AC Adapter US, 100-240V - North America Plug	811-9918-02
Go-Cal AC Adapter Euro, 100-240V	811-9918-03
Go-Cal AC Adapter UK, 100-240V	811-9918-04
Go-Cal AC Adapter Australia/NZ, 100-240V	811-9918-05
Go-Cal Manual	360-0162-01

Specifications

Range.....0.01 to 20 LPM
 Accuracy ±2% or 0.005 std. LPM, whichever is greater
 Dimensions.....5 in. × 2 in. × 1.25 in.
 Weight 2.2 lbs
 Warm Up Time.....1 Minute
 DC Power Input.....7.5 VDC ±1.5 V, 300 mA max

Each Go-Cal calibrator is shipped complete with the following:

Calibrator, Battery pack including 6-AA size alkaline batteries, Tubing kit, Carrying case, NIST traceable calibration certificate, and User guide

Doc: GoCal-DS Rev. B 082013

